

We BRIGHTEN Your BRANDS



120D1 12 VDC Power Supply

Damp/Dry-rated 120 Watt power supply

- Two (2) Class 2 60 W 12 VDC outputs
- Universal input voltage – 100-277 VAC, 50-60 Hz input
- Auto-resetting – No fuses to replace or circuit breaker to reset. Short circuit and over-current protection circuit automatically resets when condition is corrected
- Rugged and compact

SPECIFICATIONS

Part number	701507-120D1
Dimensions L x W x H	9.6 in x 2.2 in x 1.7 in
Nominal input voltage	100-277 VAC, 50-60 Hz
Maximum input current	1.7 A
Power output	120 W @ 12 VDC, two (2) 60 W Class 2 outputs (North America only)
Location rating	Dry and damp locations
Operating temperature	-40° C to +60° C, natural convection cooling
Compatibility	SloanLED 12 VDC products



SloanLED Headquarters
5725 Olivias Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED Rev C 2016-06-07

