

24 VDC Power Supply

IP68-rated 100 Watt power supply

- Patented end cap design for easy electrical connections and installation
- Auto-resetting No fuses to replace or circuit breaker to reset. Short circuit protection automatically resets when short condition is corrected
- Simple secondary hook-ups No minimum load or load balancing required
- Modular design Cluster with standard J-boxes to create multiple 100 W legs
- Rugged and compact

SPECIFICATIONS

Dimensions L \times W \times H 10.25 in \times 1.73 in \times 1.19 in Nominal input voltage..... 100-240 VAC, 50-60 Hz Maximum input current 2.0 A Power output 100 W @ 24 VDC, Class 2 output (North America only) **Location rating** Dry, damp, and wet locations **Operating temperature**......-30° C to $+60^{\circ}$ C Protection class IP68











24 VDC Power Supply (701895-24C) is covered by U.S. and foreign patents pending and covered by one or more of the following U.S. patents issued: 6,776,504, 6,969,179, 7,192,157, 6,932,495, 7,241,031

SloanLED Headquarters 5725 Olivas Park Drive • Ventura, California 93003 805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.

Overslagweg 7 • 2645 EK Delfgauw • The Netherlands +31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

